Table 3.3: Quantitative High Level Requirements

Quantity	Requirement	comment
Angular acceptance	10 mr to 300 mr	single arm, forward in
_		direction of antiproton
		beam
Charged Particle Momentum acceptance	>3 GeV	
Mass resolution (all charged state)	$< 50 \text{ MeV/c}^2$	e.g. $B_s \to D_s K$
		$D_s \to K^+K^-\pi$
Tracking efficiency	>98%	
Primary Vertex Resolution	$100~\mu\mathrm{m}$	for typical light quark event
Proper Time resolution	<50 fs	based on B_s Mixing, $x_s < 60$
		and $\Delta\Gamma$ for $B_s < 10\%$
Trigger efficiency	>50%	For B decays that would
		pass all analysis cuts with
		≥ 2 charged tracks from
		B or D vertex
	>20%	For B decays with a single
		prong at the B vertex and a
		$K_s \to \pi^+\pi^-$
Trigger rejection	99.8%	Light quark events
Maximum data rate to archival storage	<200 Mbyte/sec	
Particle id	π -K separation	$\geq 4\sigma$
	from 3 to 70 GeV	
	p-K separation	$\geq 4\sigma$
	from 3 to 70	
Electromagnetic calorimeter resolution	$<2\%\sqrt{E}$	
Electromagnetic calorimeter energy range	>1 GeV	limited by noise and
		combinatoric background
Electromagnetic calorimeter acceptance	maximum >200 mr	Almost all photons of
	minimum 10 mr	interest lie within
		this range
Muon identification	Momentum from	$\leq 200 \text{ mr due}$
	5 to 100 GeV/c	to interference with floor
Muon Misidentification	$ <10^{-3}$	
Muon Momentum Resolution	$\frac{\sigma_p}{p} = 19\% \oplus 0.6\% \times p$	For stand alone muon trigger
Luminosity	$>2x10^{32}$	
Interactions/crossing	< 6.0 >	
Time response	<100ns	to handle 132 ns bunch
		intervals
Radiation Resistance	at least 10 years	all detectors